

XTREME



UK/016/005

SPECIFICATION

Material Type	Fabrics	Durability	> 50,000 turns Martindale
Supplier	Camira	Lightfastness	> 5 (scale 1-8)
Pattern	Solid	Price Class	PC Basic
Composition	100% Xtreme FR (Polyester FR)	Flammability	EN 1021-1 & 2 (in combination with standard polyurethane 20-30 kg/m3)
Weight	310 g/m2		

ABOUT

Xtreme is a durable crepe fabric made of 100% recycled FR Polyester. The fabric is an excellent choice for working environments, schools or public environments. Xtreme Plus has good stretching properties and is durable.

COLOURS IN THE XTREME SERIES

□ Xtreme 4516



Xtreme 4524




Xtreme 4531


□ Xtreme 4552




Xtreme 4554



Xtreme 4558




Xtreme 4570




Xtreme 4583



Xtreme 4592



Xtreme 4598



Xtreme 4599

XTREME



XTREME FULFILLS THE FOLLOWING STANDARDS:

- | | | | |
|---|------------------------------------|------------------------------------|-------------------------------------|
| ✓ EN ISO 12947-2+AC 12
KPA
EN ISO 12947-2+AC 12 KPa | ✓ EN ISO 12945-2
EN ISO 12945-2 | ✓ EN ISO 105-B02
EN ISO 105-B02 | ✓ EN ISO 13936-2
EN ISO 13936-2 |
| ✓ EN ISO 105-X12
EN ISO 105-X12 | ✓ EN ISO 105-D02
EN ISO 105-D02 | ✓ EN ISO 105-D01
EN ISO 105-D01 | ✓ ISO ISO 105-C06
EN ISO 105-C06 |
| ✓ ISO ISO 105-E16
EN ISO 105-E16 | ✓ EN ISO 105-E04
EN ISO 105-E04 | ✓ EN 1021-1:2014
EN 1021-1:2014 | ✓ EN 1021:2:2014
EN 1021-2:2014 |

INSPIRATION

